CHAPTER 2: DATA MODELS

1.	A data model is usually graphical. a. True b. False
	ANSWER: True
2.	An implementation-ready data model needn't necessarily contain enforceable rules to guarantee the integrity of thedata. a. True b. False
	ANSWER: False
3.	An implementation-ready data model should contain a description of the data structure that will store the enduserdata. a. True b. False
	ANSWER: True
4.	Within the database environment, a data model represents data structures with the purpose of supporting a specific problem domain. a. True b. False
	ANSWER: True
5.	Even when a good database blueprint is available, an applications programmer's view of the data should match that of the manager and the end user. a. True b. False
	ANSWER: False
6.	In the context of data models, an entity is a person, place, thing, or event about which data will be collected andstored. a. True b. False
	ANSWER: True
7.	Database designers determine the data and information that yield the required understanding of the entire business. a. True b. False
	ANSWER: False

\mathbf{C}

b. False

ANSWER: True

hap	ter 2: Data Models
	Business rules apply to businesses and government groups, but not to other types of organizations such as religiousgroups or research laboratories. a. True b. False
	ANSWER: False
	Business rules must be rendered in writing. a. True b. False
	ANSWER: True
	In an SQL-based relational database, each table is dependent on every other table. a. True b. False
	ANSWER: False
	In an SQL-based relational database, rows in different tables are related based on common values in commonattributes. a. True b. False
	ANSWER: True
	A disadvantage of the relational database management system (RDBMS) is its inability to hide the complexities of the relational model from the user. a. True b. False
	ANSWER: False
	Each row in the relational table is known as an entity instance or entity occurrence in the ER model. a. True b. False
	ANSWER: True
	In Chen notation, entities and relationships have to be oriented horizontally; not vertically. a. True b. False
	ANSWER: False
	M:N relationships are not appropriate in a relational model. a. True

a. True b. False
ANSWER: True
17. The network model has structural level dependence.a. Trueb. False
ANSWER: True
18. The external model is the representation of the database as "seen" by the DBMS.a. Trueb. False
ANSWER: False
19. The hierarchical model is software-independent.a. Trueb. False
ANSWER: False
20. The relational model is hardware-dependent and software-independent.a. Trueb. False
ANSWER: False
21. A(n)''s main function is to help one understand the complexities of the real-world environment. a. node
22. A(n) represents a particular type of object in the real world. a. attribute b. entity c. relationship d. node ANSWER: b
23. A(n) is anything about which data are to be collected and stored. a. attribute b. entity c. relationship d. constraint ANSWER: b

24		ne equivalent of a field in a file system.
	a. attribute	b. entity
	c. relationship	d. constraint
	ANSWER: a	
25.	A(n)is bi	directional.
	a. attribute	b. entity
	c. relationship	d. constraint
	ANSWER: c	
26.	A(n)is a	restriction placed on the data.
	a. attribute	b. entity
	c. relationship	d. constraint
	ANSWER: d	
27.	are impor	rtant because they help to ensure data integrity.
	a. Attributes	b. Entities
	c. Relationships	d. Constraints
	ANSWER: d	
28.	are norma	ally expressed in the form of rules.
	a. Attributes	b. Entities
	c. Relationships	d. Constraints
	ANSWER: d	
29.	Students and cla	sses have arelationship.
	a. one-to-one	b. one-to-many
	c. many-to-one	d. many-to-many
	ANSWER: d	
30.	From a database defined	point of view, the collection of data becomes meaningful only when it reflects properly
	a. business rules	
	b. business norm	ns
	c. business goals	s
	d. business plans	s
	ANSWER: a	

31.	 a. They allow the designer to set company policies with regard to data. b. They allow the designer to develop business processes. c. They can serve as a communication tool between the users and designers. d. They provide a framework for the company's self-actualization. 		
ANSWER: c			
32.	A noun in a business rule translates to a(n)in the data model. a. entity b. attribute c. relationship d. constraint		
	ANSWER: a		
33.	A verb associating two nouns in a business rule translates to a(n)in the data model. a. entity b. attribute c. relationship d. constraint		
	ANSWER: c		
34.	The hierarchical data model was developed in thea. 1960sb. 1970s c. 1980s d. 1990s		
	ANSWER: a		
35.	The object-oriented data model was developed in thea. 1960s b. 1970s c. 1980s d. 1990s		
	ANSWER: c		
36.	VMS/VSAM is an example of the a. hierarchical model		
	ANSWER: b		
37.	Oracle 11g is an example of the a. hierarchical model b. file system data model c. relational data model d. XML/Hybrid data model		
	ANSWER: d		
38.	MySQL is an example of the a. hierarchical model b. file system data model c. relational data model d. XML data model		

Chantan 2. Data Madala			
Chapter 2: Data Models ANSWER: c			

Chap	oter 2: Data Models
	In themodel, the basic logical structure is represented as an upside-down tree. a. hierarchical b. network c. relational d. entity relationship
	ANSWER: a
	In themodel, each parent can have many children, but each child has only one parent. a. hierarchical b. network c. relational d. entity relationship
	ANSWER: a
	The relational data model was developed in thea. 1960s b. 1970s c. 1980s d. 1990s ANSWER: b
	In themodel, the user perceives the database as a collection of records in 1:M relationships, where each record can have more than one parent. a. hierarchical b. network c. object-oriented d. entity relationship
	ANSWER: b
	Themodel was developed to allow designers to use a graphical tool to examine structures rather thandescribing them with text. a. hierarchical b. network c. object-oriented d. entity relationship
	ANSWER: d
	A(n)enables a database administrator to describe schema components. a. extensible markup language (XML) b. data definition language (DDL) c. unified modeling language (UML) d. query language
	ANSWER: b
	Which of the following types of HDFS nodes stores all the metadata about a file system? a. Data node b. Client node c. Name node d. Map node ANSWER: c
46.	Which of the following types of HDFS nodes acts as the interface between the user application and the HDFS a. Data node b. Client node c. Name node d. Map node ANSWER: b

47.	 a. It does not promote data sharing. b. It is not efficient with 1:M relationships. c. It does not promote data integrity. d. It does not have standards. 		
	ANSWER: d		
48.	NoSQL databases: a. are geared toward transaction consistency; not performance. data. c. are based on the relational model.	b. support only small amounts of sparsed. provide fault tolerance.	
	ANSWER: d	d. provide fault tolerance.	
49.	Themodel uses the term connectivity to label the relational a. relational b. network c. object-oriented d. entity relationship	onship types.	
	ANSWER: d		
50.	Which of the following is true of NoSQL databases? a. They do not support distributed database architectures. model.	b. They are not based on the relational	
	c. They are geared toward transaction consistency rather than performance.	d. They do not support very large amounts of sparse data.	
	ANSWER: b		
51.	Thedata model is said to be a semantic data model. a. relational b. network c. object-oriented d. entity relationship		
	ANSWER: c		
52.	Thedata model uses the concept of inheritance. a. relational b. network c. object-oriented d. entity relationship		
	ANSWER: c		
53.	One of the limitations of themodel is that there is a lack a. hierarchical b. network c. relational d. entity relationship	c of standards.	
	ANSWER: a		
54.	Themodel is the end users' view of the data environme a. abstract b. external c. conceptual d. internal	nt.	
	ANSWER: b		

55.	An internal refers to a specific representation of an internal model, using the database constructs supportedby the chosen database.
	a. tuple b. schema
	c. object d. value
	ANSWER: b
56.	A(n)is a relatively simple representation of more complex real-world data structures.
	ANSWER: data model
57.	A(n) is a brief, precise, and unambiguous description of a policy, procedure, or principle within a specificorganization.
	ANSWER: business rule
58.	A(n)in a hierarchical model is the equivalent of a record in a file system.
	ANSWER: segment
59.	A(n)is the conceptual organization of an entire database as viewed by a database administrator.
	ANSWER: schema
60.	The relational model's foundation is a mathematical concept known as a
	ANSWER: relation
61.	Each row in a relation is called a(n)
	ANSWER: tuple
62.	Each column in a relation represents a(n)
	ANSWER: attribute
63.	A(n) defines the environment in which data can be managed and is used to work with the data in the database.
	ANSWER: data manipulation language (DML)
64.	Each row in the relational table is known as a(n)
	ANSWER: entity instance
65.	In, a three-pronged symbol represents the "many" side of the relationship.
	ANSWER: Crow's Foot notation
66.	A(n)is a collection of similar objects with a shared structure and behavior.
	ANSWER: class
67.	In object-oriented terms, a(n)defines an object's behavior.
	ANSWER: method

68. _____is a language based on OO concepts that describes a set of diagrams and symbols used to graphically modela system.

ANSWER: UML (Unified Modeling Language)

Unified Modeling Language (UML)

Unified Modeling Language

UML

69. The term_____is used to refer to the task of creating a conceptual data model that could be implemented in anyDBMS.

ANSWER: logical design

70. The ______is the representation of a database as "seen" by the DBMS.

ANSWER: internal model

71. What components should an implementation-ready data model contain?

ANSWER: An implementation-ready data model should contain at least the following components:

A description of the data structure that will store the end-user data.

A set of enforceable rules to guarantee the integrity of the data.

A data manipulation methodology to support the real-world data transformations.

72. What do business rules require to be effective?

ANSWER: To be effective, business rules must be easy to understand and widely disseminated to ensure that everyperson in the organization shares a common interpretation of the rules. Business rules describe, in simplelanguage, the main and distinguishing characteristics of the data as viewed by the company.

73. What are the sources of business rules, and what is the database designer's role with regard to business rules?

ANSWER: The main sources of business rules are company managers, policy makers, department managers, andwritten documentation such as a company's procedures, standards, and operations manuals. A fasterand more direct source of business rules is direct interviews with end users. Unfortunately, becauseperceptions differ, end users are sometimes a less reliable source when it comes to specifying businessrules. For example, a maintenance department mechanic might believe that any mechanic can initiate amaintenance procedure, when actually only mechanics with inspection authorization can perform such atask. Such a distinction might seem trivial, but it can have major legal consequences. Although end usersare crucial contributors to the development of business rules, it pays to verify end-user perceptions. Toooften, interviews with several people who perform the same job yield very different perceptions of whatthe job components are. While such a discovery may point to "management problems," that generaldiagnosis does not help the database designer. The database designer's job is to reconcile suchdifferences and verify the results of the reconciliation to ensure that the business rules are appropriate and accurate.

- 74. Describe the three parts involved in any SQL-based relational database application.
 - ANSWER: From an end-user perspective, any SQL-based relational database application involves three parts: a userinterface, a set of tables stored in the database, and the SQL "engine." Each of these parts is explained below.
 - The end-user interface. Basically, the interface allows the end user to interact with the data (byautomatically generating SQL code). Each interface is a product of the software vendor's idea of meaningful interaction with the data. You can also design your own customized interface with thehelp of application generators that are now standard fare in the database software arena.
 - 2. A collection of tables stored in the database. In a relational database, all data are perceived to bestored in tables. The tables simply "present" the data to the end user in a way that is easy tounderstand. Each table is independent. Rows in different tables are related by common values incommon attributes.
 - 3. SQL engine. Largely hidden from the end user, the SQL engine executes all queries, or datarequests. Keep in mind that the SQL engine is part of the DBMS software. The end user usesSQL to create table structures and to perform data access and table maintenance. The SQLengine processes all user requests—largely behind the scenes and without the end user'sknowledge. Hence, SQL is said to be a declarative language that tells what must be done but nothow.
- 75. Describe the conceptual model and its advantages. What is the most widely used conceptual model?
 - ANSWER: The conceptual model represents a global view of the entire database by the entire organization. That is, the conceptual model integrates all external views (entities, relationships, constraints, and processes) into a single global view of the data in the enterprise. Also known as a conceptual schema, it is the basis forthe identification and high-level description of the main data objects (avoiding any database model-specific details).

The most widely used conceptual model is the ER model. Remember that the ER model is illustrated with the help of the ERD, which is effectively the basic database blueprint. The ERD is used tographically represent the conceptual schema.

The conceptual model yields some important advantages. First, it provides a bird's-eye (macro level)view of the data environment that is relatively easy to understand.

Second, the conceptual model is independent of both software and hardware. Software independencemeans that the model does not depend on the DBMS software used to implement the model. Hardwareindependence means that the model does not depend on the hardware used in the implementation of themodel. Therefore, changes in either the hardware or the DBMS software will have no effect on thedatabase design at the conceptual level. Generally, the term logical design refers to the task of creating aconceptual data model that could be implemented in any DBMS.